



DIAMANTE

Lava

DIA-6609


18-1449 TPX




Lava
DIA-6609
18-1449 TPX




Honey
DIA-6604
17-1320 TPX



Espresso
DIA-6613
19-1118 TPX



Mercury
DIA-6622



Olive
DIA-6616
18-0435 TPX




Vintage
DIA-6623



Indigo
DIA-6618
19-3920 TPX



Carbon
DIA-6615
19-0000 TPX



Snow
DIA-6601
13-0000 TPX



Sunset
DIA-6607
17-1340 TPX



Otoño
DIA-6619
17-1319 TPX



Tonic
DIA-6621



Sage
DIA-6605
17-0610 TPX



Meteor
DIA-6614
19-3803 TPX



Regatta
DIA-6611
19-4127 TPX




Pepper
DIA-6624




Polar
DIA-6600



Ivory
DIA-6602
14-1107 TPX



Tapioca
DIA-6620



Taupe
DIA-6603
16-1406 TPX



Mulberry
DIA-6610
19-1718 TPX



Grapey
DIA-6617
19-3905 TPX

The colour samples are indicative and not intended as an exact replica of the actual colour of the product. Due to variations in monitor settings and colour



balances, colours are representative only and should not be construed as an exact colour match of the listed product. We advise you to request actual material samples before ordering.



TEXTURE DETAIL:
Scale: 1:3

TECHNICAL SPECIFICATIONS

SECTOR

AUTOMOTIVE

- ✓ Caravans & RV
- ✓ General Automotive
- ✓ Mass Transportation
- ✓ Motorcycles

CONTRACT

- ✓ Healthcare
- ✓ Hospitality
- ✓ Office
- ✓ Outdoor
- ✓ Public Spaces
- ✓ Residential

MARINE

- ✓ Marine Exteriors
- ✓ Marine Interiors

DESIGN:

Geometrics
Textile

COMPOSITION:

Vinyl / Urethane Topcoat

BACKING

PROTECTIVE FINISHES

PERMABLOK^{3®}
ADVANCED VINYL PROTECTION

WIDTH:

137.00 cm

ROLL LENGTH:

30.00 m

WEIGHT:

680.00 gr/m²

FLAME RETARDANCY ¹

- EU: EN 1021 Part 1 & 2
- US: CAL TB 117-2013, Section E
- ES: UNE 23.727-90 1R/M.2
- FR: NF P 92-503/M2
- DE: DIN 4102 B2
- IT: UNI 9175 (1987) / UNI 9175/FA1 (1994) Classe 1.1M (UNO I EMME)
- AT: ÖNORM B 3825, Gruppe 1 - Schwerbrennbares Verhalten
- AT: ÖNORM A 3800 Teil 1, Qualmbildungsklasse Q1 - schwachqualmend
- IMO FTP 2010 Code MSC.307 (88) Part 8 3.1 & 3.2
- US: FMVSS 302
- US: FAR 25/853
- (MED) Marine Equipment Directive (in its current valid version)
- ECE R118.02 (replaces Directive 95/28/CE) Annexes 6, 7 & 8
- EN 71-2:2006+A1:2007 - Safety of Toys - Parte 2: Flammability

FINISHES AND TREATMENTS

- Antibacterial Protection
- PERMABLOK^{3®}
- Anti-stain Finish
- >100.000 cycles Martindale (EN ISO 12947:1999 Part 2)
- Cold Crack -23°C
- Mildew resistant backing and face
- UV-Resistance XENOTEST DIN 54004/ NTC 1479
- EN 71-3 Safety of Toys (Migration of certain elements)
- Sulfide Stain Resistant
- Anti-static Finish

¹ This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

TERMS AND CONDITIONS OF PRODUCT

EURO SPRADLING S.L.U.
Carrer Garbí 3
Polígono industrial de Llevant | Sector C
08213 Polinyà
Barcelona, Spain

SPRADLING INTERNATIONAL GmbH
Stadtkoppel 34
D-21337
Lüneburg, Germany

SPRADLING® UK
Telephone: +44 (0) 1235 812329
Fax: +44 (0) 1235 815051
E-mail: info.uk@spradling.group

SPRADLING UK LTD
Unit 5, Moorbrook Park
Didcot, Oxfordshire, OX11 7HP
United Kingdom

SPRADLING® USA Want to know more about our products in USA?

VISIT SPRADLING USA 