



DOLCE (PU)

Tangelo

DOL-6718

18-1354 TPX




Tangelo

DOL-6718
18-1354 TPX




Grass

DOL-6722
18-0538 TPX



Jet

DOL-6724
19-4110 TPX



Meteor

DOL-6727
18-1306 TPX



White

DOL-6701
11-0602 TPX



Ecrú

DOL-6703
13-1008 TPX




Latte

DOL-6706
16-1010 TPX



Camel

DOL-6709
18-0933 TPX



Mocha

DOL-6712
18-0930 TPX



Poppy

DOL-6719
18-1449 TPX




Peacock

DOL-6723
18-4528 TPX



Indigo

DOL-6725
19-4019 TPX



Artesian

DOL-6726
16-1305 TPX




Ivory

DOL-6702
12-0703 TPX



Dune

DOL-6704
16-0920 TPX



Mushroom

DOL-6708
17-0800 TPX



Russet

DOL-6711
19-1241 TPX



Chocolate

DOL-6713
19-1314 TPX

**Burgundy**DOL-6714
19-1322 TPX**Moss**DOL-6717
19-0414 TPX**Black**DOL-6728
19-0000 TPX

The colour samples are indicative and not intended as an exact replica of the actual colour of the product. Due to variations in monitor settings and colour

balances, colours are representative only and should not be construed as an exact colour match of the listed product. We advise you to request actual material

samples before ordering.

**TEXTURE DETAIL:**
Scale: 1:3

TECHNICAL SPECIFICATIONS

SECTOR**AUTOMOTIVE**

- ✓ Caravans & RV
- ✓ General Automotive
- ✓ Mass Transportation
- ~~Motorcycles~~

CONTRACT

- ✓ Healthcare
- ✓ Hospitality
- ✓ Office
- ~~Outdoor~~
- ✓ Public Spaces
- ✓ Residential

MARINE

~~Marine-Exteriors~~
~~Marine-Interiors~~

DESIGN:

Faux Leathers

COMPOSITION:

Polyurethane

BACKING:

100% Rayon

WIDTH:

137.00 cm

ROLL LENGTH:

27.40 m

WEIGHT:

370.00 gr/m²

FLAME RETARDANCY ¹

- EU: EN 1021 Part 1 & 2
- US: CAL TB 117-2013, Section E
- IMO FTP 2010 Code MSC.307 (88) Part 8 3.1 & 3.2
- US: FMVSS 302

FINISHES AND TREATMENTS

- Antibacterial Protection
- >300,000 cycles Martindale (EN ISO 12947:1999 Part 2)
- Cold Crack -23°C
- Mildew resistant backing and face
- UV-Resistance XENOTEST DIN 54004/ NTC 1479
- EN 71-3 Safety of Toys (Migration of certain elements)
- 2005/84/EC (phthalates in toys and childcare articles)

¹ This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

TERMS AND CONDITIONS OF PRODUCT

SPRADLING® SPAIN
Telephone: +34 938 655 719
Fax: +34 938 627 960
E-mail: info.es@spradling.group

EURO SPRADLING S.L.U.
Carrer Garbí 3
Polígono industrial de Llevant | Sector C
08213 Polinyà
Barcelona, Spain

SPRADLING® UK
Telephone: +44 (0) 1235 812329
Fax: +44 (0) 1235 815051
E-mail: info.uk@spradling.group

SPRADLING UK LTD
Unit 5, Moorbrook Park
Didcot, Oxfordshire, OX11 7HP
United Kingdom

SPRADLING® GERMANY
Telephone: +49 (0)4131 7098 4000
Fax: +49 (0)4131 7098 4010
E-mail: info.de@spradling.group

SPRADLING INTERNATIONAL GmbH
Stadtkoppel 34
D-21337
Lüneburg, Germany

SPRADLING® USA Want to know more about our products in USA?

VISIT SPRADLING USA 